

Product Specifications

Patient Recliner Lift GK NOVUM 2000

mobile bathing recliner lift with electric variable height adjustment and a replaceable battery system

Description

- Mobile transfer system for lifting and transporting of people with reduced mobility
- Compatible in form and function with GK-bathtubs: Lowering the lift into the bath is possible. The user does not have to leave the lift for bathing.
- Smooth height adjustment by means of a cable-bound hand control unit and a fixed keyboard
- Electric spindle stroke drive DC 24 V
- Automatic stop of the downward movement if the seat meets with resistance while in motion
- Heavy-duty parts made of special steel, galvanized and powder coated
- Chassis covered with polyurethane
- Easily changeable and twist-proof PU foam-padded back rest
- 3-piece PU foam-padded stretcher with head rest; tilt of both side panels individually adjustable
- Middle panel with hygiene/toilet opening and cover
- Additional safety through a downwards, across the reclining surface, swivelling grip with attached safety stirrup
- Four twin steering castors; Of these one with brake and one with brake and straight-line stability lock 125 mm diameter, two normal with 100 mm diameter
- Wall mounted charger with console for battery pack
- Easy to open battery box for a fast exchange of standard battery cells
- Warning light for timely battery pack replacement
- Emergency-off switch

Technical Specifications

- Load capacity200 kg
- Net weight 70 kg
- Stroke height 630 mm

Dimensions:

- Length of chassis (side of stretcher) 1040 mm
- Length of chassis (side of handle) 900 mm
- Width of chassis 790 mm
- Overall height1220-1850 mm
- Overall length1030-1940 mm (long model: up to 2060 mm)
- Overall width990-1020 mm (with scale: 1020 mm)
- Max. width of tub edge100-130 mm
- Lowest installable stretcher height..... 190 mm (+ stroke height)
- Highest installable stretcher height 440 mm (+ stroke height)
- Net stretcher surface..... approx. 1820 x 440 mm

Electrical Data:

- Plug-in socket..... 230 V / 50 Hz supply for charger
- (115 V / 60 Hz in other countries)
- Operating voltage.....DC 24 V

Certificates

- CE mark (accordance with Annex I of the Medical Device Directive 93/42/EWG)

Make: Krämer
Type: GK NOVUM 2000
Art.No.: 2.800.00

Effective 11/2014 - Technical changes reserved!

Product Specifications

Options for GK NOVUM 2000

Safety Belt

- With clip buckle

Make: Krämer
Type: GK NOVUM 2000 SG
Art.No.: 2.100.20

Scale

- Electronic scale mounted onto lift mast
- Capacity of scale 200 kg
- Digital display with a graduation of 100 g
- Automatic tare and hold function of the weight display
- Automatic switch off
- Power supply from battery pack of the lift system

Make: Krämer
Type: GK NOVUM 2000 W
Art.No.: 2.700.50

Battery Pack Extra

- Additional battery for replacement in case of extremely high utilization

Make: Krämer
Type: GK NOVUM 2000 WA
Art.No.: 2.700.60

Adjustable Commode Opening

- Seat insert with oval opening (approx. 168 x 238 mm)

Make: Krämer
Type: GK NOVUM 2000 SO
Art.No.: 2.700.70